

FITTING INSTRUCTIONS FOR BEACON PLATE (PR3081)



Kit Contains

- 1 x Instructions
- 1 x Beacon Plate
- 2 x M6x10mm Screws
- 2 x M6x16mm Washer
- 2 x M6 T-Slot Nuts
- 1 x 4mm Allen Key

Remove parts from box & check
Contact your Prorack dealer if any parts are missing or damaged

Installation to Standard T-Slot crossbars



T-Slot crossbars similar to this



1

- Select two T-slot nuts from the package
- Press crossbar infill down and fit both T-slot nuts into crossbar on top of infill.



2

- T-slot nuts should be positioned on crossbar in a place where you want your plate to be located.



3

- Select two M6x10mm capscrews and M6x16mm washers from the package
- Put M6x16 washer under each capscrew
- Use 4mm Allen Key to attach plate to T-nuts with screws through the centre mounting holes.

Page 1 of 1



4

- Completely assembled beacon plate on crossbar in the desired position.

Warranty & disclaimer

1. Where the product is supplied to the customer for other than business purposes within the meaning of section 43 of the New Zealand Consumer Guarantees Act 1993, the provisions of that Act shall apply. It is important that anyone who fits or uses this product does so in accordance with the manufacturers instructions.

2. Where the product is supplied to the customer for business purposes within the meaning of section 43 of the New Zealand Consumer Guarantees Act 1993, the provisions of that Act shall have no effect and the clauses below shall apply. Where the product is supplied and purchased in Australia, the following shall apply:

a) **THE SUPPLIER WARRANTS** the product to be free from defects in materials and/or workmanship for a period of two (2) years from the date of original purchase (the warranty period). Proof of purchase is required. Subject to the limitations and exclusions set out below, the Supplier hereby agrees to remedy any defects in materials or workmanship becoming apparent during the warranty period, by replacing or repairing any defective product or component (at its option) free of charge to the purchaser in respect of replacement parts or labour. Any defective product or component must be notified and where practicable, returned at the purchaser's expense to the Supplier immediately upon discovery of the alleged defect and no attempt made on the part of the purchaser to repair it.

b) **EXCEPTIONS, EXCLUSIONS AND LIMITATIONS TO WARRANTY.** The product and/or its components must be fitted/assembled in accordance with the Supplier's written instructions. This warranty does not cover defects, loss or damage resulting a circumstances beyond the Supplier's control including, but not limited to misuse, overloading, or failure to assemble and/or fit the product or component in accordance with the Supplier's written instructions. Nor does the warranty cover defects, loss or damage resulting from accidents, unlawful use of the vehicle or defects/inconsistencies in the vehicle on which the product or component is fitted. Liability for direct, indirect, special, punitive, incidental, exemplary, contractual or consequential damage or loss arising from defects, faulty materials or design omissions or negligence or workmanship in the product or its components is hereby expressly excluded. Certain Commonwealth legislation, including the Trade Practices Act 1974, and other State and Territorial legislation confers upon purchasers rights which cannot be excluded from or be restricted or modified by contract. Any conditions, guarantees and/or warranties implied by law and incapable of exclusion are deemed to be expressly incorporated herein. Nothing herein contained is intended nor shall be permitted to be inconsistent with any such conditions, guarantees and/or warranties. To the extent permitted by legislation all conditions, guarantees and/or warranties such as implied warranties which are capable of exclusion are hereby expressly excluded and negated

Hubco Automotive Ltd
46 Parkhouse Road
PO Box 11-017
Christchurch 8004
New Zealand

Free phone New Zealand:
0800 4776 722
Free phone Australia:
1800 143 548